

## ROAD CONES

RAL Plastic road cones are flexible, resilient, and can absorb impact.

### CONE SIZES/TYPES:

Sports Cone	180mm base
	280mm height
Small	335mm base
	510mm height
Standard	440mm base
	750mm height
Large	520mm base
	1020mm height
Hi Line	520mm base
	1130mm height



Regulatory colours: Orange, green & yellow - Other colours available on request

## SANDWICH BOARDS

Two piece moulded, making these boards easy to manage. There is provision for attaching a flashing light and space is available for your logo or advertising.



### SPECIFICATIONS:

610mm width
1130mm to top of lamp
920mm height

Regulatory colours: Orange, green & yellow - Other colours available on request

## REFLECTIVE TAPE

Reflective tape is an essential addition for road cones of 750mm and above when used at night. Transit N.Z. road safety equipment regulations are available from us, so we can advise you of your specific needs.

Regulatory colours: The two contrasting colours should be orange & white with a diagonal stripe



### SPECIFICATIONS:

Must be up to specification class 1
Reflective material in accordance with AS/NZS 1906

## A-FRAME ROAD BARRIERS

Our barriers meet Transit N.Z. and local body requirements. Additional features of these barriers are their ability to be filled with water or sand for extra stability and incorporates a flashing light attachment.

Regulatory colours: Orange, green & yellow - Other colours available on request such as personalising barriers to your company colours



### SPECIFICATIONS:

700mm to centre of barrier board from road surface
900mm to centre of barrier board from road surface
Barrier bar = 2-2.3 metre length bars

## BARRELS

These barrels are manufactured, allowing them to come free at the base on impact. Ours are designed to hold a sandbag in the base for ballast.

Regulatory colour: Orange



### SPECIFICATIONS:

900mm min. height
600mm min. flat base
5kg unballasted weight

## INTERLOCKING ROAD BARRICADES

Interlocking barricades that can be linked to form a straight line or positioned, to a 90 degree.



### SPECIFICATIONS:

900mm min. height
1600mm length
700mm base width

Colours: A range of colours are available